



SECTION 1: Identification

**Product identifier:** Flo-Soft Special

**Other means of identification:** Fabric Softener

**SDS number:** 288

**Recommended use:** Fabric Softener

**Recommended restrictions:** Not for personal care

**Manufacturer/Importer/Supplier/Distributor information**

**Company name:** U.N.X. Incorporated

**Address:** 707 Arlington Blvd  
Greenville, NC 27858

**Telephone:** Office hour (Mon-Fri)  
8:00a.m. – 4:00p.m. (Eastern Time)  
OFFICE NUMBER: 252-756-8616

**Contact Person** Jamie Singleton

**E-mail:** Jamie@unxinc.com

**Emergency phone number:** CHEMTEL (800) 255-3924 (24 HOURS)

SECTION 2: Hazard(s) identification

**Classification of the Substance or Mixture:**

**Physical hazards** Not classified

**Health hazards**

Acute Toxicity: Category 4

Skin Corrosion/irritation: Category 3

Serious Eye damage/eye irritation: Category 3

**Label elements:**



**Signal word:** Warning

**Hazard statements**

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

## Precautionary statements

### Prevention

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P262	Do not get in eyes, skin, or on clothing.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this products.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

### Response:

P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352	IF ON SKIN: Wash with plenty of water.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use the Manufacturer/supplier or the competent authority to specify appropriate media to extinguish.

### Storage:

P403	Store in a well-ventilated place.
------	-----------------------------------

### Disposal:

P501	Dispose of contents/container in accordance with local/ regional/ national/ international Regulations.
------	--

### Hazard(s) not otherwise

Classified (HNOC) Not Classified

## SECTION 3: Composition/information on ingredients

### Substance/Mixtures

Chemical name	CAS Number	Concentration (%)	Hazardous	Chemical Characterization
Water	7732-18-5	80-95	No	Substance
Methyl bis-2-hydroxyethyl Ammonium methyl sulfate	68410-69-5	5-15	Yes	Substance
Polyethylene glycol monoisodecyl ether	61827-42-7	0-5	No	Substance
Isopropanol	67-63-0	0-1	No	Substance

## SECTION 4: First-Aid Measures

### Description of first aid measures

**General advice:** Remove victims from the danger zone without endangering your own safety. Remove contaminated clothing (including underwear and shoes) immediately.

**Inhalation:** Bring accident victims out into the fresh air. If patient has difficulty breathing, administer oxygen, keep the patient calm and warm. In case of unconsciousness place patient stably in side position for transportation. Call a physician immediately.

**Skin contact:** Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before re-use. After contact with small amounts get medical attention if any discomfort or irritation continues. For large amounts, obtain medical attention.

**Eye contact:** Immediately flush eyes with gentle but large stream of water or eye wash solution for at least 15 minutes, lifting lower and upper eyelids occasionally. If possible remove any contact lenses and continue to wash. Call a physician, immediately.

**Ingestion:** If swallowed, rinse mouth with water (only if the person is conscious). Never give anything by mouth to an unconscious person. DO NOT induce vomiting, medical advice is required. Call a physician, immediately.

### Most important symptoms/effects, acute and delayed:

**Notes to physician:** The severity of the symptoms described will vary dependant on the concentration and the length of exposure.

**Inhalation:** Irritation of nose, throat and airway.

**Ingestion:** May cause nausea and/or vomiting. Irritation of the mouth, throat, esophagus and gastrointestinal tract.

**Skin contact/Skin irritation:** Redness or rash may occur.

**Eye contact:** Causes irritation of the eyes. Possible corneal damage. May cause conjunctivitis Lachrymation. May cause burns.

### Indication of immediate medical attention and special treatment needed if necessary:

Cases of eye contact and ingestion should be treated immediately. Have facilities in place to wash skin and eyes in case of exposure.

## SECTION 5: Fire-fighting measures

**Suitable extinguishing media:** This product is flammable by OSHA criteria. In case of fire use carbon dioxide (CO<sub>2</sub>), foam, extinguishing powder. In cases of larger fires, water spray should be used. Use any means suitable for extinguishing surrounding fire. Water spray may be used to keep fire-exposed containers cool. If water is used, use in abundance to control heat.

**Unsuitable extinguishing media:** Do not use water jet as this can spread the fire. Do not use carbon dioxide in enclosed spaces with insufficient ventilation.

**Specific hazards arising from the chemical:** Fire may produce irritating, corrosive and/or toxic gases. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Move containers from fire area if you can do so without risk. Product containers can melt in the heat of a fire. Packaging materials will be combustible and provide fuel for the fire. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray. For massive fire in cargo, use unmanned hose holder or monitor nozzles. If not, withdraw and let fire burn out.

**Special protective equipment and precautions for fire-fighters:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. During fire-fighting respirator with independent air-supply and airtight garment is required. Fight fire in early stages if safe to do so. Containers at risk of fire should be cooled with water and, if possible removed from the danger area. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.

## SECTION 6: Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** Ventilate area of leak or spill. Ensure adequate ventilation/exhaust extraction. Put on protective equipment (see Section 8). Have emergency procedures in place for treating spillages, evacuating the area and informing the emergency services if necessary. Restrict access to the area until the spillage is treated, if large amounts of vapors are produced that will be hazardous to others, evacuate the area. When any other effects of spillages will affect the safety of others the area should be evacuated. Avoid ingestion, inhalation of vapors and contact with skin and eyes. Non-emergency personnel should be kept away from the area of spillage.

**Environment precautions:** Do not flush into surface water or sanitary sewers system. Avoid unauthorized discharge to the environment. Clean up any spillages immediately; prevent material from spreading and entering drains or sewage systems. Large spillages or uncontrolled discharge to water systems must be alerted to the Environmental Agency or other regulatory body. If spillages to land cannot be treated safely or if contamination will occur the Environment Agency must be alerted immediately. If the product has entered a foul drain or sewage system in significant amounts to cause a hazard then the local water treatment company must be informed.

**Methods and materials for containment and cleaning up:** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Contain and recover liquid when possible. Small spillages should be absorbed with an inert, non-combustible absorbent. Large Spillages: Dam and absorb spillages with sand, earth or other inert material. Small quantities (< 2 gallons) can be flushed to drain with lots of water. Fit drain covers where they are available if the spillage is likely to enter the drainage system. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Containers with collected spillage must be properly labeled with correct contents and hazard symbol. Flush area clean with lots of water. Be aware of potential for surfaces to become slippery. Ventilate area and allow drying before allowing access. Wash thoroughly after dealing with a spillage.

**Reference to other sections:** Refer to sections 8 and 13 for additional information.

## SECTION 7: Handling and Storage

**Precautions for safe handling:** Keep in a tightly closed container and protect from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture, incompatibilities, and away from direct sunlight. Do not mix with incompatible substances or mixtures. Avoid spilling the product. Do not wash out container and use it for other purposes. Avoid ingestion of the product, inhalation of any vapors/mists when produced and contact with skin and eyes. Do not eat, drink or smoke when handling. Wash at the end of each work shift, before eating, drinking, smoking and using the toilet. Remove contaminated clothing/footwear/equipment before entering eating areas or places that would expose others to the product. Do not use in areas close to drainage systems unless measures are in place to prevent access of product. Ensure emergency procedures are in place to treat spillages and cope with other situations such as evacuation. Provide eye washing and skin washing facilities, when handling large amounts a safety shower is recommended. Observe all warnings and precautions listed for the product.

**Conditions for safe storage, including any incompatibilities:** Store in closed original container at temperatures between 40°F and 80°F. If the product is transferred to another container, this should be made of a compatible material to the original container. Store away from heat, direct sunlight and moisture. Store in a stable situation to avoid spillages. It is advisable to store in a bunded area or use other protective measures such as a sump pallet or storage tray.

## SECTION 8: Exposure control/personal protection

### Control Parameters

#### Occupational exposure limits

##### US.OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Chemical Name	CAS-No.	Type	ppm	mg/m <sup>3</sup>
Isopropanol	67-63-0	PEL	400 ppm	980 mg/m <sup>3</sup>
Polythethylene glycol	25322-68-3	TWA		10 mg/m <sup>3</sup>

##### U.S. ACGIH Threshold Limit Values

Chemical Name	CAS-No.	Type	ppm	mg/L
Isopropanol	67-63-0	BEI		40 mg/L
		STEL	400 ppm	
		TWA	200 ppm	

### Appropriate engineering controls:

#### Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the defined exposure limit requirements or guidelines. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition for details.

### Individual protection measures, such as personal protective equipment (PPE)

**Eye Protection:** Use chemical safety goggles and/or full face shield where dusting or splashing of

solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

**Skin Protection:** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Hand protection:** Wear protective gloves. Butyl rubber, rubber (natural, latex), nitrile, polyvinyl chloride (PVC). Be aware that latex gloves can produce an allergic reaction in sensitive individuals. Gloves should have a breakthrough time sufficient for the amount of handling but allow dexterity for safe movement and handling. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Gloves showing signs of degradation should be changed to avoid skin contamination. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. When removing used gloves apply proper technique by avoiding skin contact with the outer surface. When packages of the product are being handled during storage or transport it is advisable to wear protective gloves to prevent damage to the skin.

**Personal Respirators (NIOSH Approved):** If the exposure limit is exceeded, a full face piece respirator with high efficiency dust/mist filter may be worn up to 50 times the exposure limit. Wear suitable respiratory protection when vapors or mists are produced if the Workplace Exposure Limit is exceeded and there is insufficient ventilation or extraction. For emergencies or instances where the exposure levels are not known, use a full face piece positive-pressure, air-supplied respirator. Respirator must be fitted with a cartridge suitable for the chemical of concern. Consult with the supplier as to the compatibility of the equipment with the chemical of concern. CAUTION: Air purifying respirators do not protect the user in oxygen deficient atmospheres, use air supplied system.

**Thermal Hazards:** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations:** Wash hands, change out of clothes as soon as possible. Wash clothes. Shower or bathe as soon as possible.

**Other protective measures:** Have an eye bath and safety shower close by.

## SECTION 9: Physical and chemical properties

<b>Appearance:</b>	Liquid
<b>Colour:</b>	Creamy white liquid
<b>Odour:</b>	Fresh fragrance
<b>Odour Threshold:</b>	No data available
<b>pH:</b>	5 ± 0.5
<b>Melting point/range:</b>	No data available
<b>Boiling point/range:</b>	No data available
<b>Flash point:</b>	N/A
<b>Evaporation rate:</b>	No data available
<b>Flammability (solid, gas):</b>	No data available
<b>Upper/lower flammability of explosive limits:</b>	No data available
<b>Vapour pressure (mm Hg):</b>	No data available
<b>Vapour density (Air=1):</b>	No data available
<b>Relative density:</b>	No data available
<b>Solubility(ies):</b>	Excellent in warm water
<b>Partition coefficient (n-octanol/water):</b>	No data available
<b>Auto-ignition temperature:</b>	No data available
<b>Decomposition temperature:</b>	No data available
<b>Viscosity, dynamic:</b>	18

**Other Information:** This product contains no phosphates.

## SECTION 10: Stability and Reactivity

**Reactivity and/or Chemical stability:** If stored and handled in accordance with standard industrial practices no hazardous reactions are known. Product is very stable under normal conditions.

**Possibility of hazardous reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Avoid heat, direct sunlight, and moisture. Avoid storage with incompatible materials. Avoid storage in freezing conditions. Avoid storage near to unprotected drainage systems. Avoid storage in an unstable manner or in a situation that would result in exposure to the product. It is advisable to store the product within some form of containment to prevent spillages reaching drainage systems. Do not allow the storage container to be left exposed to the atmosphere.

**Incompatible Materials:**

-Strong oxidizers      -Strong acids      -Strong bases      -Chlorine

**Hazardous Decomposition Products:** Mild decomposition can result giving off hydrogen.

## SECTION 11: Toxicological information

**Acute toxicity:** Toxicological testing has not been conducted with this material. The toxicology information listed below us based on the components of this material.

Methyl bis-2-hydroxyethyl ammonium methyl sulfate
Acute Toxicity Estimate (ATE)
ATE <sub>Mix</sub> (oral) >2,000 mg/kg

**Skin Corrosion/ irritation:** May cause irritation of the skin. Not known to be corrosive.

**Serious eye damage/irritation:** May cause irritation and serious eye damage.

**Respiratory or skin sensitization:**

**Respiratory sensitization:** Classification not possible.

**Skin sensitization:** Classification not possible.

**Germ cell mutagenicity:** Classification not possible.

**Carcinogenicity:** Classification not possible.

**Reproductive toxicity:** Classification not possible.

**Specific Target Organ Toxicity - Single Exposure:** Classification not possible .

**Specific Target Organ Toxicity - Repeated Exposure:** Classification not possible .

**Aspiration hazard:** Classification not possible .

### Information on the likely routes of exposure

**General information:** Effects will be dependent upon the concentration and length of time of exposure. Higher concentrations will produce more pronounced effects.

**Inhalation:** Vapors or mists may irritate the nose, throat and respiratory tract. May cause coughing and difficulties with breathing.

**Ingestion:** Irritation of the mouth, the esophagus and the gastrointestinal tract. Stomach pain and vomiting may occur.

**Skin contact:** May cause irritations of the skin.

**Eye contact:** Causes irritation of the eyes. May cause corneal damage and lacrimation. Conjunctivitis may develop. Risk of serious damage to eyes.

## SECTION 12: Ecological information

Do not allow to escape into waterways, wastewater or soil.

**Toxicity:** Ecotoxicological studies of the product are not available. Please find below the data available to us from raw materials:

### Aquatic ecotoxicity

Isopropanol
LC50 Bluegill ( <i>Lepomis macrochirus</i> ) >1,400 mg/L Fresh Water: 96 hrs

**Persistence and Degradability:** No data is available on the degradability of this product.

**Bioaccumulative Potential:** No data available for this product.

**Mobility in Soil:** Not available.

**Other adverse effects:** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13: Disposal considerations

### General information

Do not allow unauthorized disposal to the environment. If operators are exposed to vapors during the disposal process then suitable respiratory protection should be worn. All other personal protective equipment as described in section 8 should be worn.

### Disposal methods:

Avoid unauthorized disposal. Do not dump into any sewers, on the ground, or into any body of water. All disposal practices must be in compliance with federal, state/provincial and local laws and regulations. For a



small spill, immediately hose down with cool water and dispose to drain. For a large spill, dike, collect and contact local authorities about disposal.

#### SECTION 14: Transport Information

UN Number:	Not Available
UN Proper Shipping Name:	Not Applicable
Transport hazard class(es):	
DOT Hazard Class:	Not Available
DOT Subsidiary Hazard Class:	Not Available
Packing group, if available:	Not Available
Environmental Hazards:	No
Special precautions for user:	Not DOT regulated.

Transport in bulk according to Annex II of MARPOL 73/78<sup>3</sup> and the IBC Code <sup>3</sup>: Not applicable

#### SECTION 15: Regulatory Information

##### Safety, health and environmental regulations/legislation specific for the substance or mixture

Unless otherwise noted, no components are SARA TITLE 3 SECTION 313 40 CFR listed materials.

The ingredients of this product are listed on the TSCA inventory.

This product is not made with VOC'S that could cause damage to the ozone layer.

##### State Regulations

##### US- New Jersey RTK- Substances: Listed substance

Isopropanol (CAS 67-63-0)

Substance no. 1076

#### SECTION 16: Other Information including date of preparation or last revision

Chemical State: Liquid	Issue Date:	4-16-2014
Chemical Type: Mixture	Revision Date:	-
	Version #:	01

To the best of our knowledge, the information contained herein is accurate. **However, neither U.N.X. Incorporated nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.** Final determination of suitability of any material is the sole responsibility of the user. All materials may represent unknown hazards and should be used within caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.